

A A C

TAM ALÜMİNYUM İLETKENLER ALL ALUMINIUM CONDUCTORS



GOST 839

Kod Adı Code Name	Nominal Kesit Nominal Area		Tel Wires		Dış Çap Overall Diameter mm	Kopma Gerilmesi Ultimate Strength N	DC Direnç Resistance at 20°C Ohms/km	Yaklaşık Ağırlık Approx. Weight kg/km	Standard Yükleme Standard Shipment		
	AWG or circ.mils	mm ²	Adet Number	Çap Diameter mm					Uzunluk Length m	Net Ağırlık Net Weight kg	Makara Tipi Type of Reel
16	31360	15,9	7	1,70	5,1	2 736	1,8376	43	6 800	300	C
25	47860	24,9	7	2,13	6,4	4 109	1,1650	68	4 500	300	C
35	67810	34,3	7	2,50	7,5	5 609	0,8502	94	3100	300	C
50	97650	49,5	7	3,00	9,0	7 767	0,5880	135	4 100	550	TA
70	129900	69,3	7	3,55	10,7	10 699	0,1204	189	3 000	550	TA
95	184100	92,4	7	4,10	12,3	13 856	0,3147	252	2 150	550	TA
120	230900	117,0	19	2,80	14,0	19 623	0,2510	321	3 400	1 100	E
150	190300	148,0	19	3,15	15,8	24 124	0,1978	406	2 700	1 100	E
185	358400	182,8	19	3,50	17,5	29 832	0,1611	502	2 200	1 100	E
240	478600	238,7	19	4,00	20,0	37 814	0,1230	655	1650	1 100	E
300	590900	288,3	37	3,15	22,1	160954	0,1017	794	1 750	1 400	EH
350	682400	345,8	37	3,45	24,2	56 408	0,0848	952	1 500	1 450	EH
400	789600	389,2	37	3,66	25,6	63 420	0,0756	1072	1 500	1 600	EH
450	886300	441,9	37	3,90	27,3	69 760	0,0665	1 218	1 400	1 700	EH
500	986400	500,4	37	4,15	29,1	79 189	0,0587	1378	1 600	2 200	FC
550	1073600	544,0	61	3,37	30,3	88 660	0,0540	1500	1 500	2 250	FC
600	1158050	586,8	61	3,50	31,5	95 632	0,0503	1 618	1 400	2 250	FC
650	1266400	641,7	61	3,66	32,9	104 575	0,0459	1 771	1 300	2 300	FC
700	1365100	691,7	61	3,80	34,2	112 725	0,0425	1 902	1 200	2 300	FC
750	1475000	747,4	61	3,95	35,6	118 324	0,0393	2 062	1 100	2 300	FC
800	1589100	805,2	61	4,10	36,9	127 183	0,0365	2 220	1 000	2 220	FC